



Backhoe Loader Capacity : 1.1 cu.m./0.24 cu.m. Engine : Kirloskar 4R1040, 96 HP







Specifications

PhanTom 4x4


Engine	4WD (4x4), KIRLOSKAR 4R1040TA (BS III) 4 cylinder, turbo charged, water cooled diesel engine delivering 96 HP @ 2200 rpm	Turning RadiusWithout BrakeWith Brake	4.4 metres 3.5 metres
Max Torque	400 Nm@1400 rpm	Refill Capacities	
Transmission	Synchro shuttle transmission with torque converter & synchronised gear box. Single switch forward- reverse function for better loading application with 4 forward & 4 reverse speeds. Max speed 40 kmph	 Hydraulic Tank: Fuel Tank: Engine Oil: Transmission & Torque Converter: 	90 ltrs. 150 ltrs. 11.5 ltrs. 17 ltrs.
Axle	Front : Drive (In case of 4 WD) & Steer Axle, centrally pivoted Rear : Rigid axle with CARRARO planetary drive.	 Rear Axle (Planetary gear box): Differential Housing: Tyres 	3 ltrs. 14.5 ltrs
Steering	Hydrostatic steering for reliability and better control.	• Front 2WD : 4WD :	9.00 - 16 – 16 PR 12.5 / 80 – 18-12 PR
Brakes	Hydraulically actuated wet disc brakes at rear wheels with twin pedals in cabin for better control. Mechanically actuated disc brakes for parking.	 Rear - Standard Optional Equipment 	 16.90 - 28 – 12 PR 6-in-1 loader bucket Rock Breaker
Cabin	ROPS fully enclosed wide view cabin with easy entry and exit from the cabin.		 Excavator bucket : 0.09 cu.m./ 0.12 cu.m. & 0.30 cu.m. Heavy Duty Tyres (14.00 x 25) A.C. Cabin
Hydraulic System	Main Pump flow : 118 lpm Relief Pressure : 225 bar		 Telematics
Electrical System	12V Battery with negative earth and suitable alternator.	Variant Model	Kirloskar 4R1040TC 4 cylinder, inline water cooled turbo charged engine delivering 76 HP @ 2200 rpm
Operating weight	8040 kgs.		300 Nm @ 1400 rpm

Dimensions

PhanTom 4x4









Static Dimensions

A. OVERALL LENGTH	6.2 M
B. OVERALL HEIGHT	3.6 M
C. HEIGHT TO TOP OF CAB	2.9 M
D. WHEEL BASE	2.18 M
E. MIN GROUND CLEARANCE	0.35 M
F. SLEW GROUND CLEARANCE	0.66 M
WIDTH (OVER BUCKET)	2.50 M
TRACK WIDTH FRONT	1.84 M
TRACK WIDTH REAR	1.55 M

Loader Performance

A. DUMP HEIGHT AT 40°	2.96 M
B. LOADOVER HEIGHT	3.35 M
C. BUCKET PIN HEIGHT	3.63 M
D. REACH AT GROUND	1.77 M
E. REACH AT FULL HEIGHT BUCKET DUMPED (40°)	0.89 M
F. BELOW GROUND LEVEL DIG DEPTH	0.08 M
X. MAX. REACH AT FULL HEIGHT	1.22 M
G. ROLLBACK AT GROUND	44 °
H. DUMP ANGLE	45°
LOADER BREAKOUT FORCE BUCKET	5200 kgf
PAY LOAD	1900 kg
LOADER BUCKET CAPACITY (STD)	1.1 cu.m




Excavator Performance I. MAX. DIG DEPTH 4.60 M J. REACH GROUND LEVEL TO REAR WHEEL CENTER 6.80 M K. REACH GROUND LEVEL TO SLEW CENTER 5.50 M L. MAX. WORKING HEIGHT 5.80 M M. MAX. LOADOVER HEIGHT 3.35 M N. REACH AT FULL HEIGHT TO SLEW CENTER 2.78 M **O. BUCKET ROTATION POWER** 175° P. SIDE REACH TO CENTER LINE OF MACHINE 5.59 M Q. KING POST TRAVEL 0.9 M R. REACH GROUND LEVEL TO STABILISER START POINT 4.45 M S. FULL OPERATING HEIGHT 4.13 M 5700 kgf BUCKET TEAROUT FORCE 0.30 cum EXCAVATOR BUCKET CAPACITY (STD)





RELIABLE AND DEPENDABLE EFFICIENCY



NETWORK



MARKETING H.Q.

4th Floor, Pinnacle Surajkund, NCR-121009 Ph. : +91-129-4550000 Fax : +91-129-4550022 E-mail: marketing@ace-cranes.com
 REGISTERED OFFICE

 Dudhola Link Road, Dudhola

 Palwal-121102, Haryana

 Ph.: +91-1275-280111

 Fax: +91-1275-280133

 CIN : L74899HR1995PLC053860

MUMBAI OFFICE

31, "Kalpataru Court" Chembur, Mumbai - 400074 Ph.: +91-22-25206846, 25207070 Fax: +91-22-25207071 E-mail: acemumbai@ace-cranes.com **KOLKATA OFFICE**

"Forma Towers" 84-A, Second Floor AJC Bose Road, Kolkata - 700014 Ph.: +91-9038070630 E-mail: acekolkatta@ace-cranes.com

CHENNAI OFFICE

1st Floor, "Alsa Regency", 165 Eldams Road, Alwar Pet Chennai - 600018 Ph.: +91-44-24314253 Fax: +91-44-24314252 E-mail: acechennai@ace-cranes.com

HERE TO SERVE YOU.

SPARE PARTS & SERVICE

ACE has all India Sales and Service network operating out of all the major cities. These outlets are fully equipped to provide genuine spare parts and services by company trained engineers. These outlets are further supported by company officials based at Delhi, Mumbai, Chennai, Kolkatta, Ahmedabad, Surat, Pune, Jaipur, Chandigarh, Ranchi, Raipur, Indore, Bhubneshwar, Lucknow, Jamnagar, Hyderabad, Bangalore,Guwahati, Patna, Vizag & Kochi.





ACE reserves the right to alter any specifications without prior notice. Dimensions, weights & capacities mentioned herein are variable by \pm 5%. Accessories if shown are not part of the Standard Equipment.